

<b>x2</b>	
<b>Rider Weight and cargo limits*</b>	
Max. Payload (Rider Plus all Cargo)	260 lbs / 117 kg
Min. Rider Weight	100 lbs / 45 kg
Max. Handlebar Cargo Weight	10 lbs / 4.5 kg
<b>Performance</b>	
Max. Speed	12.5 mph / 20 km/h
Energy (Rechargeable Batteries)	Litium Ion (Li-ion)
Range on a Full Charge**	9 to 12 mi
	14 to 19 km
Turning Radius	Zero. The Wheels can rotate in opposite
	directions, enabling the Segway PT to
	turn in place.
Tire Inflation Pressure	4 psi
Power Requirements	100 to 240 V~;
Worldwide	50 or 60 Hz
<b>Dimensions</b>	
Machine Weight Without Batteries	94 lbs / 44 kg
Ground Clearance (Unloaded)	4.4 in / 11.2 cm
Machine Length and Width	26.5 X 33 in
	67 X 84 cm
Handlebar Height from Mat	38 - 43 in
	97 - 109 cm
Handlebar Height from Ground (Unloaded)	47 - 52 in
	119 - 132 cm
Powerbase height (Unloaded)	9 in / 22.9 cm
Tire Diameter	21 in / 53.3 cm
Tire Type	All-terrain
<b>InfoKey Controller</b>	
Battery	CR2430 replacement batteries are available at Electronics stores.
<b>Specification for Batteries</b>	
<b>Charging Time</b>	
Before First Use	12 hours
Recharge from Empty:	~8 hours
<b>Temperature Ranges</b>	
Operating	14 F to 122 F (-10 C to 50 C)
Charging	14 F to 122 F (-10 C to 50 C)
Storage and Transport	-4 F to 122 F (-20 C to 50 C)
<b>General</b>	
Capacity (Ah) and Voltage	5.8 Ah, 73.6 V~
Dimensions	14 x 7.5 x 3.2 in (35.7 x 19 x 8.2 cm)
Battery Pack Weight (pair)	22.7 lbs (10.3 kg)
<b>Safety</b>	
Redundant electrical systems	
Robust mechanical systems	

**Wide Platform:** The wide base platform is optimized for rider comfort.

**Rugged Tires:** Deep tread, ATV style tires traverse all sorts of terrain -- confidently get where you're going

**Cargo Handles:** Oversized cargo handles make for easy lifting and provide mounting points for accessories

<b>i2</b>	
<b>Rider Weight and cargo limits*</b>	
Max. Payload (Rider Plus all Cargo)	260 lbs / 117 kg
Min. Rider Weight	100 lbs / 45 kg
Max. Handlebar Cargo Weight	10 lbs / 4.5 kg
<b>Performance</b>	
Max. Speed	12.5 mph / 20 km/h
Energy (Rechargeable Batteries)	Lithium Ion (Li-ion)
Range on a Full Charge**	16 to 24 mi 26 to 39 km
Turning Radius	Zero. The Wheels can rotate in opposite directions, enabling the Segway PT to turn in place.
Tire Inflation Pressure	15 psi
Power Requirements	100 to 240 V~;
Worldwide	50 or 60 Hz
<b>Dimensions</b>	
Machine Weight Without Batteries	82 lbs / 37 kg
Ground Clearance (Unloaded)	3.4 in / 8.5 cm
Machine Length and Width	25.5 X 25 in 65 X 63 cm
Handlebar Height from Mat	38 - 43 in 97 - 109 cm
Handlebar Height from Ground (Unloaded)	46 - 51 in 117 - 130 cm
Powerbase height (Unloaded)	8 in / 20 cm
Tire Diameter	19 in / 48.3 cm
Tire Type	Standard
<b>InfoKey Controller</b>	
Battery	CR2430 replacement batteries are available at Electronics stores.
<b>Specification for Batteries</b>	
<b>Charging Time</b>	
Before First Use	12 hours
Recharge from Empty:	~8 hours
<b>Temperature Ranges</b>	
Operating	14 F to 122 F (-10 C to 50 C)
Charging	14 F to 122 F (-10 C to 50 C)
Storage and Transport	-4 F to 122 F (-20 C to 50 C)
<b>General</b>	
Capacity (Ah) and Voltage	5.8 Ah, 73.6 V~
Dimensions	14 x 7.5 x 3.2 in (35.7 x 19 x 8.2 cm)
Battery Pack Weight (pair)	22.7 lbs (10.3 kg)
<b>Safety</b>	
Redundant electrical systems	
Robust mechanical systems	

**Wide Platform:** The wide base platform is optimized for rider comfort

**Leansteer:** Quick removal allows for easy storage

**Gliding Lights:** Ensure your PT can be readily seen in low light conditions